KRUPPS DISHWASHER MACHINES

SINCE 1965

100% MADE IN ITALY



ADVANCE RANGE C432

TYPE	Glasswasher
LINE	ADVANCE RANGE
BASKET	400x400
SIZE	470x535x710h

Reliability and ease of use: these are the key words of the **ADVANCE** line. The panel is the real strength of the line thanks to its **4 washing cycles** and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the dishwasher status very easily. The simple and extremely efficient electronic card offers the possibility of setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

The **C432** model, available with round basket or with square basket, is suitable for washing cups, glasses, saucers and dishes (using the appropriate basket) with a clearance of up to 295 mm, using a single 120-second standard cycle.

The standard **double electric rinse-aid and detergent dispenser** ensures maximum hygiene at each wash cycle with great savings: the **moulded washing and rinsing arms** ensure reliability and durability. The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

CERTIFIED

ON REQUEST

KRUPPS
DISHWASHER MACHINES


50 SINCE 1965

100% MADE IN ITALY

DISHWASHERS FEATURES	ADVANCE RANGE C432
Dimensions - (mm) L - P - H	470x535x710h
n° baskets/hour - (+55°C)	30
Height glass max	285mm
Ø height plate max	305mm
Tank heating element - Tank capacity	2,6kW - 17lt
Boiler heating element - Boiler capacity	2,5kW - 3,2lt
Washing pump	0,26kW / 0,35Hp
Total power input / Current	2,86kW / 16A
Standard input voltage	230V 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
ACCESSORI	
Saucer holder 12 pieces	1
Cutlery insert	1
Basket for glasses dim.400x400x150mm	2
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Booster pump kit 0,5Hp	●
pompa_di_scarico_installata_4_w	●
Reverse osmosis system	-
Inclined basket for wine glasses dim.400x400x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
ADVANCE display	●
"SOFT Door" Opening/Closing System	●
Kit with 2 Baskets and Stand	●

● Optional Installabile, - Optional not installable

C432



CERTIFIED

ON REQUEST