



EVOLUTION RANGE

EVO301

| | |
|--------|---------------------------|
| TYPE | Rack conveyor dishwashers |
| LINE | EVOLUTION RANGE |
| BASKET | 500x500 |
| SIZE | 1968x813x1615h |

The EVOLUTION Line has been designed to meet the needs of every customer, thanks to the various accessories installable, combining large workloads and optimising spaces available, simplifying operator work and reducing consumption. The models of this line are equipped with a double filtration system that retains all residues, whereas the vertical wash pumps and stainless steel wash arms ensure great performance. Evolution is also equipped with counterbalanced doors with double wall and anti-fall system and rounded moulded tanks.

The range (with standard installed break-tank), is equipped with integrated pre-wash to remove even the more difficult impurities, combining efficiency and reduced water consumption. Electricity and water consumption adapts to the productivity required to constantly optimise costs as needed. The double flow wash pump ensures great pressure even against stubborn dirt, while the pre-wash deals with larger residues, gathering them into a drawer filter that is easy to empty. The drying area uses the low temperature air to gently treat even the most sensitive dishes. The 450 mm useful opening allows the introduction of a wide range of dishes, dough trays, baking trays pots and various utensils.

| DISHWASHERS FEATURES | EVOLUTION RANGE EVO301 |
|---|--------------------------|
| Dimensions - (mm) L - P - H | 1968x813x1615h |
| Basket dimensions | 500x500 |
| n° baskets/hour | 200/100 |
| Passage height max (cm) | 450 |
| Total power input | 23,2 (55°C) 32,7 (15°C)* |
| Standard input voltage | 400V3N+T 50 Hz |
| PRELAVAGGIO | |
| Tank capacity | 69 |
| FIRST WASHING | |
| Tank heating element (kW) | 10,5 |
| WASHING | |
| Tank capacity | 69 |
| resistenza_vasa | 10,5 |
| FINAL RINSING | |
| Boiler heating element (kW) | 9,5 |
| Water consumption | ~300 |
| Inlet water temperature (°C) | +55°C |
| Minimum water pressure (BAR) | 1,5 |
| Water hardness (°f) | 7÷10 °f |
| STANDARD EQUIPMENT | |
| Basket for glasses dim.500x500x100mm | 1 |
| Basket for 18 dishes dim.500x500x100mm | 2 |
| 4 division cutlery insert | 1 |
| OPTIONAL | |
| Pressure reducer with pressure gauge | ● |
| Break-Tank and 200W rinse pump | ● |
| Third speed | ● |
| Corner pre-washing system | ● |
| Corner dryer unit | ● |
| Option extra power 9,5 Kw | ● |
| modulo_condensa_vapori | ● |
| estrattore_di_vapore_con_ventola | ● |
| camino_uscita_vapori | ● |
| Internal detergent & rinse-aid dosing unit | ● |
| triplo_filtro_in_vasca_e_cassetto_in_acciaio_inox | ● |

● Optional Installabile, ▢ Optional not installabile

EVO301

