



ADVANCE RANGE C327

| | |
|--------|-----------------|
| TYPE | Glasswasher |
| LINE | ADVANCE RANGE |
| BASKET | 350x350 |
| SIZE | 420x485x660h mm |

Reliability and ease of use: these are the key words of the **ADVANCE** line. The panel is the real strength of the ADVANCE line thanks to its **4 washing cycles** and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the dishwasher status very easily. The simple and extremely efficient electronic card offers the possibility of setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

The **C327** model is the most appropriate choice to wash cups, saucers and glasses in a very tight space.

The standard **double electric rinse-aid and detergent dispenser** ensures maximum hygiene at each wash cycle with great savings: the **moulded washing and rinsing arms** ensure reliability and durability. The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

EN IEC 63136 COMPLIANT MODEL

View the [performance table](#)

| DISHWASHERS FEATURES | ADVANCE RANGE C327 |
|--|--------------------|
| Dimensions - (mm) L - P - H | 420x485x660h mm |
| n° baskets/hour - (+55°C) | max 40 |
| Height glass max | 240 mm |
| Tank heating element - Tank capacity | 2,6 kW - 13 l |
| Boiler heating element - Boiler capacity | 2,5 kW - 3,2 l |
| Washing pump | 0,19 kW - 0,25 hp |
| Total power input / Current | 2,79 kW - 16 A |
| Standard input voltage | 230V1N - 50 Hz |
| Recommended inlet water temperature | +55°C |
| Water hardness | 7÷10 °f |
| Water consumption per cycle (inlet suggested pressure 2 BAR) | 2 l |
| Adjustable detergent and rinse-aid dispenser | STANDARD |
| STANDARD EQUIPMENT | |
| Basket for glasses dim.350x350x150mm | 2 |
| Saucer holder 12 pieces | 1 |
| Cutlery insert | 1 |
| OPTIONAL | |
| UNIKO touch display with IKLOUD Wi-Fi control | - |
| Booster pump kit 0,5Hp | ● |
| Drain pump kit 32W with Ecoclean | ● |
| Reverse osmosis system | - |
| Kit 4 Stainless steel feet 50-70mm | ● |
| Kit with 2 Baskets and Stand | ● |

● Optional Installabile, - Optional not installabile

C327

