



# ADVANCE RANGE C432-S

TYPE	Glasswasher
LINE	ADVANCE RANGE
BASKET	400x400
SIZE	470x595x710h mm

Professional glasswasher with **integrated automatic water softener**, ideal for washing cups, glasses, and plates with a useful clearance up to **310 mm**, ensuring **high performance and protection against limescale**. The softener automatically manages regeneration cycles based on water hardness and activates during the wash cycle without interrupting operation. The only required action is salt refilling, indicated on the display. The **ADVANCE** control panel offers 4 wash cycles and one automatic drain cycle (with installed pump), for practical and immediate use. The display allows control of temperatures, diagnostic messages, and machine status via the **SMART START** button. The electronic board manages times and temperatures with activation of the **Thermostop** functions to ensure optimal results. The standard **dual detergent and rinse aid dispenser** ensures hygiene and savings. Structure made of **AISI 304 stainless steel**, with front-facing components for simplified maintenance.

**MODEL COMPLIANT WITH EN IEC 63136 :**

See the [performance chart](#).

DISHWASHERS FEATURES	ADVANCE RANGE C432-S
Dimensions - (mm) L - P - H	470x595x710h mm
n° baskets/hour - (+55°C)	Max 40
Height glass max	285 mm
Ø height plate max	305 mm
Tank heating element - Tank capacity	2,6 kW - 17 l
Boiler heating element - Boiler capacity	2,5 kW - 3,2 l
Washing pump	0,26 kW - 0,35 hp
Total power input / Current	2,86 kW - 16 A
Standard input voltage	230V1N - 50 Hz
Recommended inlet water temperature	+55°C
Water hardness	>15° - 40°f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,4 l
Adjustable detergent and rinse-aid dispenser	STANDARD
Built-in water softener	STANDARD
<b>STANDARD EQUIPMENT</b>	
Saucer holder 12 pieces	1
Cutlery insert	1
Basket for glasses dim.400x400x150mm	2
Salt funnel	1
<b>OPTIONAL</b>	
UNIKO touch display with IKLOUD Wi-Fi control	-
Drain pump kit 32W with Ecoclean	●
Inclined basket for wine glasses dim.400x400x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
2 baskets for glasses Ø400mm	●
Optional Three-phase 400V3N+T - Boiler resistance 4,0kW	●
"SOFT Door" Opening/Closing System	●
Kit with 2 Baskets and Stand	●

● Optional Installabile, - Optional not installable

## C432-S

