



# ADVANCE RANGE C537T

TYPE	Undercounter warewasher
LINE	ADVANCE RANGE
BASKET	500x500
SIZE	585x600x815h

Reliability and ease of use: these are the key words of the **ADVANCE** line. The **ADVANCE** panel is the real strength of the line thanks to its **4 washing cycles** and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the dishwasher status very easily. The simple and extremely efficient electronic card offers the possibility of setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

With the **C537T** dishwasher you can wash glasses of different shapes and sizes, as well as 18 dishes per wash with max Ø of 395mm thanks to the baskets provided, with a maximum productivity of 40 baskets/hour (720 dishes/hour).

The standard **double electric rinse-aid and detergent dispenser** ensures maximum hygiene at each wash cycle with great savings: the **moulded washing and rinsing arms** ensure reliability and durability. The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

## EN IEC 63136 COMPLIANT MODEL

View the [performance table](#)

DISHWASHERS FEATURES	ADVANCE RANGE C537T
Dimensions - (mm) L - P - H	585x600x815h
n° baskets/hour - (+55°C)	max 40
Height glass max	365mm
Ø height plate max	395mm
Trays	GN 1/1 (special basket required)
Tank heating element - Tank capacity	2,6kW - 22lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,52kW / 0,7Hp
Total power input / Current	5,92kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7°F - 10°F
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,4 l
Adjustable detergent and rinse-aid dispenser	STANDARD
<b>STANDARD EQUIPMENT</b>	
Cutlery insert	2
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	1
<b>OPTIONAL</b>	
UNIKO touch display with IKLOUD Wi-Fi control	-
Booster pump kit 0,5Hp	●
Drain pump kit 32W with Ecoclean	●
Boiler heating element 9kW	●
Double wall for thermal and acoustic insulation +18mm	●
Stainless steel tank filter	●
Basket for trays with 4 compartments dim.500x500x200mm	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
"SOFT Door" Opening/Closing System	●
Start Cycle "SOFT Start"	●
"DOUBLE Load" double basket support	●
● Optional Installabile,    ▢ Optional not installabile	

## C537T

