



ADVANCE RANGE C640

TYPE	Undercounter warewasher
LINE	ADVANCE RANGE
BASKET	500x600
SIZE	585x715x865

Reliability and ease of use: these are the key words of the **ADVANCE** line. The **ADVANCE** panel is the real strength of the line thanks to its **4 washing cycles** and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the dishwasher status very easily. The simple and extremely efficient electronic card offers the possibility of setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

C640 is a compact warewasher, a real bonus in undercounter installations for restaurateurs who have to wash quite a few dishes (max 22/basket), baking trays and trays in a very tight space. In fact, thanks to the dedicated basket, you can wash GN 1/1 65 mm high baking trays, 600x400 dough trays and cake trays, while maintaining the measurements of a comfortable undercounter dishwasher. With its powerful washing pump and Ø30mm washing impellers, removing stubborn dirt will no longer be a problem.

The standard **double electric rinse-aid and detergent dispenser** ensures maximum hygiene at each wash cycle with great savings: the **moulded washing and rinsing arms** ensure reliability and durability. The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

EN IEC 63136 COMPLIANT MODEL

View the [performance table](#)

DISHWASHERS FEATURES	ADVANCE RANGE C640
Dimensions - (mm) L - P - H	585x715x865
n° baskets/hour - (+55°C)	max 40
Height glass max	340mm
Ø height plate max	370mm
Height pot max	340mm
Trays	Special basket required
Tank heating element - Tank capacity	2,6kW - 30lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,9kW / 1,2 Hp
Total power input / Current	6,52kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7°F - 10°F
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,4 l
Adjustable detergent and rinse-aid dispenser	STANDARD
STANDARD EQUIPMENT	
Cutlery insert	2
Basket for trays 10/12 compartments 500x600x100mm	1
Basket for glasses dim.500x600x100mm	1
Basket for 22 dishes dim.500x600x100mm	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Optional 230V/3+T	●
Booster pump kit 0,5Hp	●
Drain pump kit 32W with Ecoclean	●
Boiler heating element 9kW	●
Boiler heating element 9kW	●
Double wall for thermal and acoustic insulation +18mm	-
Basket for trays with 4 compartments dim.500x500x200mm	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
"SOFT Door" Opening/Closing System	-
Start Cycle "SOFT Start"	-

● Optional Installabile, - Optional not installabile

C640

