



# ADVANCE RANGE CH150

TYPE	Pass-through dishwasher
LINE	ADVANCE RANGE
BASKET	500x600
SIZE	720x770x1470/1930h

Reliability and ease of use: these are the key words of the **ADVANCE** line. The **ADVANCE** panel is the real strength of the line thanks to its **4 washing cycles** and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the dishwasher status very easily. The simple and extremely efficient electronic card offers the possibility of setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

The **CH150** hood-type dishwasher can wash up to 22 pizzas dishes in a very tight space: only 720 mm wide while maintaining the same depth of traditional inlet/outlet stainless steel tables, with a maximum productivity of 60 baskets/hour (1320 dishes/hour). Thanks to the **powerful wash pump** and washing arms, it is suitable for dishes, objects, bread baskets, GN 1/1 and 600x400 baking trays as its basket can fit utensils measuring up to 500x600x410(h)mm. The hood-type models are fitted with an easily removable basket support for easy cleaning and a **rounded moulded tank with integral filters** for perfect draining and absolute hygiene. The **"PUSH TO START"** cycle start system ensures less waste preventing the start of empty washes.

The electronic control allows you manage various parameters to give you a complete customisation level belonging to your needs. Thanks to the **Thermo-stop** function checks that washing and rinsing begin only when the desired temperature is reached. The standard **double electric rinse-aid and detergent dispenser** ensures maximum hygiene at each wash cycle with great savings: the **moulded washing and rinsing arms** ensure reliability and durability. The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

EN IEC 63136 COMPLIANT MODEL  
 View the [performance table](#)

DISHWASHERS FEATURES	ADVANCE RANGE CH150
Dimensions - (mm) L - P - H	720x770x1470/1930h
n° baskets/hour - (+55°C)	Max 60
Ø height plate max	400mm
Height pot max	395mm
LT bread basket	60 (H=400mm)
Trays	GN1/1 - 60x40
Tank heating element - Tank capacity	4,5kW - 37lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	1,34kW / 1,8Hp
Total power input / Current	6,74 kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7°F - 10°F
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,4 l
Adjustable detergent and rinse-aid dispenser	STANDARD
STANDARD EQUIPMENT	
Basket for trays 10/12 compartments 500x600x100mm	1
Basket for glasses dim.500x600x100mm	1
Basket for 22 dishes dim.500x600x100mm	1
8 division cutlery insert	1
Integral tank filter	STANDARD
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Optional 230V/3+T	●
Booster pump kit 0,5Hp	●
Drain pump kit 32W with Ecoclean	●
Boiler heating element 9kW	●
Boiler heating element 9kW	●
Basket for trays with 4 compartments dim.500x500x200mm	●
Remote control with LCD display	●
"Energy Pro Green" System	●
● Optional Installabile,    ▢ Optional not installable	

## CH150

