



# KORAL NORTH AME K1100E-A

TYPE	Pass-through dishwasher
LINE	KORAL NORTH AMERICA
BASKET	500x500 (20"x20")
SIZE	620x770x1435/1900 - 24"½W x 30"¼D x 74¾H

Designed to offer maximum control, versatility and productivity, the **K1100E-A** is the pass-through dishwasher from the **KORAL** line, equipped with a **UNIKO touch display** in tempered glass. The interface enables intuitive and immediate management, with access to a **wide range of wash cycles** and constant machine status monitoring via the **SMART START** button. The **electronic board** allows full parameter customization and, thanks to the **Thermostop** function, ensures that washing and rinsing begin only once the desired temperature is reached. With a useful height of **440 mm**, K1100E-A washes **plates, glasses, utensils, various objects and GN 1/1 trays**. The **PUSH TO START** system prevents accidental starts and reduces consumption. The pressed tank with **rounded bottom** and **integral filters** ensures maximum hygiene, and the removable rack support allows quick cleaning. The **continuous self-diagnosis** detects anomalies in real time, reducing downtime. The **double peristaltic dispenser** ensures accurate dosing of detergent and rinse aid, guaranteeing hygiene at every cycle. Made of **AISI 304 stainless steel**, with front-accessible components for simplified maintenance and long-lasting durability.

This model is **ETL certified** as it complies with the **UL Std.921** requirements.

DISHWASHERS FEATURES	KORAL NORTH AMERICA K1100E-A
Dimensions - (mm) L - P - H	620x770x1435/1900 - 24"½W x 30"¾D x 74¾"H
n° baskets/hour - (+55°C)	Max 60
Height glass max	390mm
Ø height plate max	415mm
LT bread basket	40 (H=390mm)
Trays	GN1/1
Tank heating element - Tank capacity	4,5kW - 37lt (9.8gal)
Boiler heating element - Boiler capacity	5,4kW - 7,3lt (1.9gal)
Washing pump	1,34kW / 1,5Hp
Total power input / Current	6,52kW / 30A
Standard input voltage	208/220V - 50/60Hz - 1HP
Recommended inlet water temperature	+55°C (125°F)
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Packing	710x960x1520h - 1,04 - 120kg (265lbs)
STANDARD EQUIPMENT	
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2
8 division cutlery insert	1
Integral tank filter	2
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Drain pump kit 32W with Ecoclean	●
Basket for trays with 4 compartments dim.500x500x200mm	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	-
● Optional Installabile, - Optional not installabile	

## K1100E-A

