



KORAL NORTH AME K1500E-A

TYPE	Pass-through dishwasher
LINE	KORAL NORTH AMERICA
BASKET	500x600
SIZE	720x770x1435/1900h - 28.3465x30.315x56.4

Designed to reduce consumption by optimizing every wash cycle, **K1500E-A** offers a **higher load capacity** than standard models: it can wash **up to 22 pizza plates per cycle** and bulky items up to **500x600x410h mm**. The **UNIKO touch display** in tempered glass enables intuitive and quick interaction, with access to a **wide variety of cycles** and machine status monitoring via the **SMART START** button. The **electronic board** allows advanced parameter adjustment and activates the **Thermostop** function to start rinsing only once the desired temperature is reached. With a productivity of **60 racks/hour**, it is perfect for handling high workloads and mixed wash cycles, including **GN 1/1 trays, 600x400 trays, and bread baskets**. The **PUSH TO START** system avoids waste and prevents accidental starts. The removable rack support and the **pressed tank with rounded bottom and integrated filters** make daily cleaning simple and fast. The **standard dual dispenser** ensures precise dosing of detergent and rinse aid. The **end-of-day self-cleaning cycle** protects the tank and boiler from limescale. The wash and rinse arms are built to ensure long-lasting performance. The structure is made of **AISI 304 stainless steel** with front-accessible components.

This model is **ETL** certified as it complies with the requirements of **UL Std.921**.

DISHWASHERS FEATURES	KORAL NORTH AMERICA K1500E-A
Dimensions - (mm) L - P - H	720x770x1435/1900h - 28.3465x30.315x56.4961/56.4961in
n° baskets/hour - (+55°C)	Max 60
Ø height plate max	400mm
LT bread basket	60 (H=400mm)
Trays	GN1/1 - 60x40
Tank heating element - Tank capacity	4,5kW - 37lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	1,64kW / 2,2Hp
Total power input / Current	7,04 kW / 16A
Standard input voltage	208V - 60Hz, 230V3 - 60Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Packing	800x980x1520h 1,19/162
STANDARD EQUIPMENT	
Basket for trays 10/12 compartments 500x600x100mm	1
Basket for glasses dim.500x600x100mm	1
Basket for 22 dishes dim.500x600x100mm	1
8 division cutlery insert	1
Integral tank filter	2
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Drain pump kit 32W with Ecoclean	●
Basket for trays with 4 compartments dim.500x500x200mm	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	-
● Optional Installabile, - Optional not installabile	

K1500E-A

