



# KORAL NORTH AME K209E-A

TYPE	Glasswasher
LINE	KORAL NORTH AMERICA
BASKET	400x400 (14" x 14")
SIZE	470x535x710h (18"½W x 21"¾D x 38"H )

**K209E-A** is the undercounter glasswasher from the **KORAL** line, designed to offer total control of the washing functions through the intuitive **UNIKO touch display** in tempered glass. The interface allows the selection of a **wide range of wash cycles**, adapting the program to different operational needs. The **electronic board** enables precise control of parameters, while the **Thermostop** function ensures that washing and rinsing only occur when the desired temperature is reached. With a usable height of **310 mm**, K209E is suitable for washing **cups, glasses, saucers, and plates** (with the dedicated rack). Electronic control allows various parameters to be managed for complete customization, and continuous self-diagnosis minimizes downtime by suggesting operations to check. The **dual detergent and rinse aid dispenser** included as standard ensures **hygiene and efficiency** through accurate dosing. The end-of-day **self-cleaning cycle** drains the tank and boiler, reducing limescale build-up. The wash and rinse arms ensure consistently high performance. The structure is made entirely of **AISI 304 stainless steel**, with front-accessible components for fast and easy maintenance.

This model is ETL certified as it complies with the requirements of **UL Std.921**.

DISHWASHERS FEATURES	KORAL NORTH AMERICA K209E-A
Dimensions - (mm) L - P - H	470x535x710h (18 <sup>1</sup> / <sub>2</sub> "W x 21 <sup>3</sup> / <sub>4</sub> "D x 38"H )
n° baskets/hour - (+55°C)	Max 48
Height glass max	285mm
Ø height plate max	305mm
Tank heating element - Tank capacity	2,6kW - 17lt (4.5gal)
Boiler heating element - Boiler capacity	2,5kW - 3,2lt (0.9gal )
Washing pump	0,26kW / 0,35Hp (1/3HP)
Total power input / Current	2.79kW - 16A - 1PH
Standard input voltage	208/220V - 50/60Hz
Recommended inlet water temperature	+55°C - ½ GPC (2.6LPC) 125°F
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Packing	670x700x880h (26½"W x 22½"D x 34½"H ) - 0,34 - 48kg (105lbs)
<b>STANDARD EQUIPMENT</b>	
Saucer holder 12 pieces	1
Cutlery insert	1
Basket for glasses dim.400x400x150mm	2
<b>OPTIONAL</b>	
UNIKO touch display with IKLOUD Wi-Fi control	-
Drain pump kit 32W with Ecoclean	●
Double wall for thermal and acoustic insulation +18mm	●
Inclined basket for wine glasses dim.400x400x170mm	●
Kit 4 Stainless steel feet 50-70mm	●

● Optional Installabile, - Optional not installabile

## K209E-A

