



# KERA RANGE KE40U

|        |              |
|--------|--------------|
| TYPE   | Glasswasher  |
| LINE   | KERA RANGE   |
| BASKET | 400x400      |
| SIZE   | 470x535x710h |

Elegant, intelligent and fully equipped, the **KE40U** is the undercounter glasswasher designed to deliver **maximum efficiency in compact spaces** with over **30% energy savings** compared to equivalent models. Equipped with the most advanced features as standard, KE40U ensures **flawless results** and high hygiene in every cycle. The **5" vertical TFT display** enables intuitive and fast management, with a **wide variety of cycles**, parameter control and real-time monitoring of status and detergents. The **Acquatech System** ensures constant pressure, temperature and flow, while the **Level Control System** keeps the tank water level always optimal. Built-in **Bluetooth and Wi-Fi** allow for remote control. The **Thermostop** system ensures that washing and rinsing phases start only when the correct temperatures are reached, guaranteeing **impeccable hygiene**. With a **310 mm clearance**, KE40U is ideal for cups, glasses, saucers and plates. Its cutting-edge design enhances the look of any environment. The **AISI 304 stainless steel structure**, **insulated double walls**, **SOFT Door** and **SOFT Start** complete a reliable machine ready to meet future challenges.

**MODEL COMPLIANT WITH EN IEC 63136 :**

See the [performance chart](#).

| DISHWASHERS FEATURES   | KERA RANGE KE40U |
|--|------------------|
| Dimensions - (mm) L - P - H                                  | 470x535x710h     |
| n° baskets/hour - (+55°C)                                    | Max 48           |
| Height glass max   | 285mm            |
| Ø height plate max   | 305mm            |
| Tank heating element - Tank capacity                         | 2,6kW - 17lt     |
| Boiler heating element - Boiler capacity                     | 2,6kW - 3,9lt    |
| Washing pump   | 0,26kW / 0,35Hp  |
| Total power input / Current                                  | 2,86kW / 16A     |
| Standard input voltage                                       | 230V - 50Hz      |
| Recommended inlet water temperature                          | +55°C            |
| Water hardness   | 7÷10°f           |
| Water consumption per cycle (inlet suggested pressure 2 BAR) | 2 l              |
| Adjustable detergent and rinse-aid dispenser                 | STANDARD         |
| Acquatech system rinse                                       | STANDARD         |
| <b>STANDARD EQUIPMENT</b>                                    |                  |
| Saucer holder 12 pieces                                      | 1                |
| Cutlery insert   | 1                |
| Basket for glasses dim.400x400x150mm                         | 2                |
| <b>OPTIONAL</b>  |                  |
| UNIKO touch display with IKLOUD Wi-Fi control                | -                |
| Drain pump kit 32W with Ecoclean                             | -                |
| Double wall for thermal and acoustic insulation +18mm        | -                |
| Reverse osmosis system                                       | ●                |
| Inclined basket for wine glasses dim.400x400x170mm           | ●                |
| Kit 4 Stainless steel feet 50-70mm                           | ●                |
| 2 baskets for glasses Ø400mm                                 | ●                |
| "SOFT Door" Opening/Closing System                           | -                |
| Start Cycle "SOFT Start"                                     | -                |
| Kit with 2 Baskets and Stand                                 | ●                |
| Wi-Fi connection module                                      | -                |

● Optional Installabile, - Optional not installabile

## KE40U

