



# KERA RANGE KE40UT

|        |              |
|--------|--------------|
| TYPE   | Glasswasher  |
| LINE   | KERA RANGE   |
| BASKET | 400x400      |
| SIZE   | 470x535x710h |

The warewashers of the **Kera** range combine **technology**, **design** and **excellent performance** with a strong focus on **sustainability**. Equipped with the latest technology as standard, they guarantee perfect washing and impeccable hygiene in every cycle. Thanks to **Integrated Bluetooth and Wi-Fi connectivity**, each model can be fully managed remotely via the **Krupps Remote Control** app and **iKloud** digital platform.

The **Kera** range is designed to offer you maximum cleanliness with a **savings of over 30% on daily energy consumption**.

The innovative three-phase glasswasher **KE40UT** represents the excellent fusion of **advanced technology**, **attractive design** and **first-class warewashing performance**, offering a complete solution for the needs of bars, wine stores and restaurants.

The handy **TFT touchscreen display vertical** offers an unprecedented control experience, making every step intuitive. The **Acquatech System** technology ensures constant temperature, pressure and consumption, while the “**Level Control**” **self-regulating system** keeps the water level in the tank constant. The **310 mm working height** allows you to clean cups, glasses, saucers and plates with precision.

The model **KE40UT** also stands out for its **remarkable energy savings**, ensuring impeccable cleaning and eco-efficiency. With its **advanced connectivity**, it is the ideal solution for the cleaning needs of the future.

| DISHWASHERS FEATURES   | KERA RANGE KE40UT |
|--|-------------------|
| Dimensions - (mm) L - P - H                                  | 470x535x710h      |
| n° baskets/hour - (+55°C)                                    | Max 48            |
| Height glass max   | 285mm             |
| Ø height plate max   | 305mm             |
| Tank heating element - Tank capacity                         | 2,6kW - 17lt      |
| Boiler heating element - Boiler capacity                     | 4,5kW - 3,9lt     |
| Washing pump   | 0,26kW / 0,35Hp   |
| Total power input / Current                                  | 2,86kW / 16A      |
| Standard input voltage                                       | 400V3N - 50Hz     |
| Recommended inlet water temperature                          | +55°C             |
| Water hardness   | 7÷10°f            |
| Water consumption per cycle (inlet suggested pressure 2 BAR) | 2 l               |
| Adjustable detergent and rinse-aid dispenser                 | STANDARD          |
| Acquatech system rinse                                       | STANDARD          |
| STANDARD EQUIPMENT   |                   |
| Saucer holder 12 pieces                                      | 1                 |
| Cutlery insert   | 1                 |
| Basket for glasses dim.400x400x150mm                         | 2                 |
| OPTIONAL   |                   |
| UNIKO touch display with IKLOUD Wi-Fi control                | -                 |
| Drain pump kit 32W with Ecoclean                             | -                 |
| Double wall for thermal and acoustic insulation +18mm        | -                 |
| Reverse osmosis system                                       | ●                 |
| Inclined basket for wine glasses dim.400x400x170mm           | ●                 |
| Kit 4 Stainless steel feet 50-70mm                           | ●                 |
| 2 baskets for glasses Ø400mm                                 | ●                 |
| "SOFT Door" Opening/Closing System                           | -                 |
| Start Cycle "SOFT Start"                                     | -                 |
| Kit with 2 Baskets and Stand                                 | ●                 |
| Wi-Fi connection module                                      | -                 |

● Optional Installabile, - Optional not installabile

## KE40UT

