



KERA RANGE KE50UT

TYPE	Undercounter dishwasher
LINE	KERA RANGE
BASKET	500x500
SIZE	600x600x815h

The warewashers of the Kera range combine **technology, design and excellent performance** with a strong focus on **sustainability**. Equipped with the latest technology as standard, they guarantee perfect washing and impeccable hygiene in every cycle. Thanks to **Integrated Bluetooth and Wi-Fi connectivity**, each model can be fully managed remotely via the **Krupps Remote Control** app and **iKloud** digital platform.

The **Kera** range is designed to offer you maximum cleanliness with a **savings of over 30% on daily energy consumption**.

The **KE50UT** three-phase dishwasher from the **Kera** range is a concentrate of technology, design and excellent warewashing performance. The **vertical TFT touchscreen display** makes it easy to manage each step and to choose and customise the most suitable cycle for every need. The **Acquatech System** technology ensures constant temperature, pressure and consumption, while the **self-regulating system "Level Control"** keeps the water level in the tank constant. The **working height of 385 mm** allows precise cleaning of plates, glasses and trays with a productivity of up to **40 baskets/hour**.

The **KE50UT** ensures **extraordinary cleanliness** and considerable energy savings, making it the ideal choice for bars, wine shops, restaurants and all establishments looking for **superior performance**.

DISHWASHERS FEATURES	KERA RANGE KE50UT
Dimensions - (mm) L - P - H	600x600x815h
n° baskets/hour - (+55°C)	Max 40
Height glass max	365mm
Ø height plate max	385mm
Trays	GN1/1 - Special basket required
Tank heating element - Tank capacity	2,6kW - 24lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,52kW / 0,7Hp
Total power input / Current	5,92kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
STANDARD EQUIPMENT	
Cutlery insert	2
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Drain pump kit 32W with Ecoclean	-
Double wall for thermal and acoustic insulation +18mm	-
Reverse osmosis system	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
2 baskets for glasses Ø400mm	●
"SOFT Door" Opening/Closing System	-
Start Cycle "SOFT Start"	-
"DOUBLE Load" double basket support	●
Wi-Fi connection module	-
● Optional Installabile, - Optional not installabile	

KE50UT

