



KERA RANGE KE60UT

TYPE	Undercounter dishwasher
LINE	KERA RANGE
BASKET	500x600
SIZE	585x715x865

KE60UT is the full-optional multifunction dishwasher from the **KERA** line, designed to handle mixed loads in compact spaces with a **high level of technological excellence**. The usable height of **405 mm** allows the washing of **plates, utensils, GN1/1 trays**, crates, and 600x400 mm trays, while maintaining the compact footprint of an undercounter machine. The modern design is combined with the intelligence of a fully connected system, with integrated **Wi-Fi and Bluetooth** for complete remote management, from setup to maintenance. The **5" vertical TFT display** allows selection from a **wide variety of programs**, customization of cycles, and **real-time monitoring** of machine status. The **Acquatech System** technology maintains constant pressure, flow rate, and temperature, while the **Level Control System** autonomously adjusts the water level in the tank. The **active self-diagnosis** promptly reports any anomalies and guides the operator, minimizing downtime. The **Thermostop** ensures that washing and rinsing begin only once the ideal temperatures are reached, for impeccable hygiene. KE60UT is equipped with **insulated double walls**, **SOFT Door**, **SOFT Start**, and an **inclined molded tank**. The **AISI 304 stainless steel** structure ensures strength and long-lasting durability, while its technologies enable **up to 30% savings on daily energy consumption**.

MODEL COMPLIANT WITH EN IEC 63136 :
 See the [performance chart](#).

DISHWASHERS FEATURES	KERA RANGE KE60UT
Dimensions - (mm) L - P - H	585x715x865
n° baskets/hour - (+55°C)	Max 40
Height glass max	360mm
Ø height plate max	385mm
Height pot max	360mm
Trays	GN1/1 - 60x40
Tank heating element - Tank capacity	2,6kW - 30lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,9kW / 1,2Hp
Total power input / Current	6,52kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
STANDARD EQUIPMENT	
Cutlery insert	2
Basket for trays 10/12 compartments 500x600x100mm	1
Basket for glasses dim.500x600x100mm	1
Basket for 22 dishes dim.500x600x100mm	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
Drain pump kit 32W with Ecoclean	-
Reverse osmosis system	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	●
"SOFT Door" Opening/Closing System	-
Start Cycle "SOFT Start"	-
Wi-Fi connection module	-

● Optional Installabile, - Optional not installabile

KE60UT

